

## POWER OPERATED HYDRAULIC PRESSES

Simple Operation : Press is provided with motorised pump unit and a hand - operate, control valve.  
 Pump is driven by flange coupled motor and has a pressure adjusting valve for adjustment of high pressure.  
 High quality hydraulic : Cyclinder is made of special steel that secures absolute pressure tightness.  
 The seals are made of special material and guarantee long life. PISTON ROD & PISTON HEAD are carefully ground and hard chrome plate to obtain closest accuracy in guiding.  
 Precision Pressing : Actual pressure may be read in tons from the precision pressure gauge that has red zone from maximum pressure and upwards. Press bed are planned off and as standard equipment.  
 2 PLANED OFF STRAIGHTEN V BLOCK are supplied



Model No.	Pressure in Tons	Between Column Length x Breadth mm mm	Between Ram to Bed Min. Max. mm mm	Travel of Ram mm	Motor H. P.
SMHP1	5	600x175	125x750	125	1.5
SMHP2	10	625x200	150x750	140	1.5
SMHP3	15	650x200	150x750	145	2
SMHP4	25	825x325	175x900	175	2
SMHP5	40	950x375	175x900	190	3
SMHP6	50	1000x415	175x900	200	3
SMHP7	60	1050x340	175x900	205	3
SMHP8	80	1125x525	175x900	220	3
SMHP9	100	1200x625	175x900	230	5
SMHP10	150	1250x675	175x1000	300	7.5
SMHP11	200	1300x700	175x1000	320	10